## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application.

## Listing of Claims:

- 1. (Previously Presented) Process for the treatment of production crude comprising the following stages:
  - (a) separation of the crude into gas and degassed emulsion phases, and
- (b) separation of the said degassed emulsion into water and oil, in which stage (b) is implemented without recovery of a flow from the emulsion interface.
- (Original) Process according the claim 1, in which stage (b) comprises the substage (b1) of washing the said emulsion with water at the oil/water interface.
- (Previously Presented) Process according to claim 1, in which stage (b) comprises substage (b2) of stripping with gas.
- (Previously Presented) Process according to claim 1, in which stage (b) comprises the substage (b3) of washing the said emulsion with water at the gas/oil interface.
- (Previously Presented) Process according to claim 1, also comprising a stage (c) of settling the oil originating from stage (b).
- 6. (Original) Process according to claim 1, in which stage (b) includes a settling operation.
- (Previously Presented) Process according to claim 1, in which stage (b) comprises a stage of passing the degassed emulsion to the bottom of a washing vessel.
- (Previously Presented) Process according to claim 7, which comprises using a water leg comprises from 3 to 15 meters.
- 9. (Previously Presented) Process according to claim 7, in which the degassed emulsion has a water content from 15 to 35 vol%.
- 10. (Previously Presented) Process according to claim 1, in which stage (a) comprises a substage (a1) of high or medium pressure separation and a stage (a2) of low pressure separation.
- (Previously Presented) Process according to claim 1, in which stage (a) is implemented at a temperature of between 35 and 75°C.

- 12. (Previously Presented) Process according to claim 1, in which the said stage (a) is implemented in less than 10 minutes.
- 13. (Previously Presented) Process according to claim 1, in which stage (b) is implemented in a time of between 4 and 24 hours.
- 14. (Previously Presented) Process according to claim 1, in which the production of crude is a complex crude.
- ${\it 15.} \qquad \hbox{(Previously Presented)} \qquad \quad \hbox{Apparatus for the treatment of production crude} \\ {\it comprising:}$
- (a) a unit (102; 108) for separation of the crude into gas and degassed emulsion phases, and
- (b) a vessel (112) for separating the said degassed emulsion into water and oil, in which the separating tank (112) does not include recovery of a flow from the emulsion interface.
- 16. (Original) Apparatus according to claim 15, in which the vessel (112) comprises a spray or water distribution system (115) for washing the said emulsion with water at the oil/water interface.
- (Original) Apparatus according to claim 16, in which the spray or wash water distribution system (115) comprises a plurality of pipes (121a, 121b, 121c) connected together in the form of a manifold.
- (Previously Presented) Apparatus according to claim 15, also comprising a distributor (116) for stripping gas at the bottom of the vessel (112).
- 19. (Previously Presented) Apparatus according to claim 15, also comprising a spray or water distribution system (117) for washing the said emulsion with water at the gas/oil interface.
- 20. (Previously Presented) Apparatus according to claim 15, also comprising a settler (114) downstream from the vessel (112).
- (Original) Apparatus according to claim 15, in which said vessel comprises a settler for settling the degassed emulsion.
- (Previously Presented) Apparatus according to claim 15, in which said vessel comprises a feed (111) for said degassed emulsion at the bottom of said vessel.
- (Previously Presented) Apparatus according to claim 22, which comprises a
  water leg from 3 to 15 meters.

3

- 24. (Previously Presented) Apparatus according to claim 22, comprising a water make-up device upstream of the feed (111).
- (Previously Presented) Apparatus according to claim 15, comprising a high or medium pressure separator (102) and a low pressure separator (108).
  - Canceled.
- 27. (Previously Presented) Ship or barge comprising the apparatus according to claim 15, the separation unit (102; 108) being on the topsides while the vessel (112) or settler is in the hull.
- 28. (Withdrawn) Process for the separation of a water-in-oil hydrocarbon emulsion comprising the following stages:
  - creation of an oil/water interface,
  - (ii) washing the said emulsion with water at the oil/water interface, and
  - (iii) recovery of a flow of oil and a flow of water.
- (Currently Amended) <u>Process for the separation of a water-in-oil hydrocarbon</u> emulsion comprising the following stages:
  - (i) creation of an oil/water interface,
  - (ii) washing the said emulsion with water at the oil/water interface, and
  - (iii) recovery of a flow of oil and a flow of water, Process according to claim 28 in which stage (iii) is implemented without recovering a flow from the emulsion interface.
- (Withdrawn) Process according to claim 28, also comprising a stage (iv) of stripping with gas.
- 31. (Withdrawn) Process according to claim 28, also comprising a stage (v) of washing the said emulsion at the gas/oil interface.
- 32. (Withdrawn) Process according to claim 28, also comprising a stage (vi) of settling the fluid from stage (iii).
- (Previously Presented) Process according to claim 29, in which stage (i)
   comprises a stage of passing the degassed emulsion to the bottom of a washing vessel.
- 34. (Previously Presented) Process according to claim 33, which comprises using a water leg comprised from 3 to 15 meters.
- 35. (Previously Presented) Process according to claim 33, in which the degassed emulsion has a water content from 15 to 35 vol%.

- 36. (Withdrawn) Process for the separation of a water-in-oil hydrocarbon emulsion comprising the following stages:
  - (i) passing the degassed emulsion to the bottom of a washing vessel, and
  - (ii) recovery of a flow of oil and a flow of water.
- (Withdrawn) Process according to claim 36, which comprises using a water leg comprises from 3 to 15 meters.
- 38. (Withdrawn) Process according to claim 36, in which the degassed emulsion has a water content from 15 to 35 vol%.
- (Currently amended) Process for the separation of a water-in-oil hydrocarbon emulsion comprising the following stages;
  - (i) passing the degassed emulsion to the bottom of a washing vessel, and
- (ii) recovery of a flow of oil and a flow of water, Process according to claim 36 in which stage (ii) is implemented without recovering a flow from the emulsion interface.
- (Withdrawn) Process according to claim 36, also comprising a stage (vi) of settling the fluid from stage (ii).
- 41. (Withdrawn) Apparatus for the separation of a water-in-oil hydrocarbon emulsion comprising a vessel (112) fitted with a spray or water distribution system (115) for washing the said emulsion with water at the oil/water interfaced.
- 42. (Withdrawn) Apparatus according to claim 41, in which the spray or wash water distribution system (115) comprises a plurality of pipes (121a, 121b, 121c) connected together in a manifold arrangement.
- (Withdrawn) Apparatus according to claim 41, also comprising a distributor
   (116) for stripping gas at the bottom of the vessel (112).
- 44. (Withdrawn) Apparatus according to claim 41, also comprising a spray or water distribution system (117) for washing the said emulsion with water at the gas/oil interface.
- (Withdrawn) Apparatus according to claim 41, also comprising a settler (114) downstream from the vessel (112).
- (Withdrawn) Apparatus according to claim 41, also comprising a vessel (112) fitted with a feed (111) for said emulsion at the bottom of said vessel.

- 47. (Withdrawn) Apparatus for the separation of a water-in-oil hydrocarbon emulsion comprising a vessel (112) fitted with a feed (111) for said emulsion at the bottom of said vessel, and further comprising downstream of said vessel (112) a settler (114).
- 48. (Withdrawn) Apparatus according to claim 47, which comprises a water leg from 3 to 15 meters.
- (Withdrawn) Apparatus according to claim 47, comprising a water make-up device upstream of the feed (111).
  - 50-51. (Canceled)
- (Withdrawn) Ship or barge comprising the apparatus according to claim 41 in the hull.